

IN THE CLAIMS

1. (currently amended) A method for conducting a perfusion study, said method comprising:

performing an initial full computed tomography scan of an area of interest in an object; and

performing at least one subsequent partial computed tomography scan of the area of interest to detect motion of a contrast agent.

2. (original) A method in accordance with Claim 1 wherein said performing at least one subsequent partial scan comprises:

performing a first full rotation including  $n$  sub-rotations, where no scanning is performed for all sub-rotations except an  $i$ th sub-rotation in which a scan is performed; and

performing a second full rotation including  $m$  sub-rotations where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed.

3. (original) A method in accordance with Claim 2 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  sub-rotations where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed wherein  $m = n$ , and  $j = i$ .

4. (original) A method in accordance with Claim 2 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  sub-rotations where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed wherein  $m = n$ , and  $j \neq i$ .

5. (original) A method in accordance with Claim 2 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  sub-rotations where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed wherein  $m \neq n$ , and  $j = i$ .

6. (original) A method in accordance with Claim 2 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  sub-rotations

where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed wherein  $m \neq n$ , and  $j \neq i$ .

7. (original) A method in accordance with Claim 2 further comprising:

collecting projection data from the partial scans;

forming a partial projection dataset from the collected projection data;

interpolating the partial projection data to estimate a complete projection dataset from the partial dataset; and

reconstructing images from the estimated complete projection dataset.

8. (original) A method in accordance with Claim 1 wherein said performing at least one subsequent partial scan comprises:

performing a first full rotation including  $n$  view-indexes, where no scanning is performed for all view-indexes except every  $i$ th view-index beginning with a view-index  $q$  in which a scan is performed; and

performing a second full rotation including  $m$  view-indexes where no scanning is performed for all view-indexes except every  $j$ th view-index beginning with a view-index  $r$  in which a scan is performed.

9. (original) A method in accordance with Claim 8 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  view-indexes where no scanning is performed for all view-indexes except every  $j$ th view-index beginning with a view-index  $r$  in which a scan is performed, wherein  $r = q$ .

10. (original) A method in accordance with Claim 8 wherein said performing a second full rotation comprises performing a second full rotation including  $m$  view-indexes where no scanning is performed for all view-indexes except every  $j$ th view-index beginning with a view-index  $r$  in which a scan is performed, wherein  $r \neq q$ .

11. (original) A method in accordance with Claim 8 further comprising:

collecting projection data from the partial scans;

reconstructing at least two images from the collected projection data;  
extrapolating an initial guess image based on the at least two images; and  
constructing subsequent images based on the extrapolated initial guess image.

12. (currently amended) A Computed Tomography (CT) System comprising:

~~a radiation~~ an x-ray radiation source;

~~a radiation~~ an x-ray radiation detector; and

a computer coupled to said radiation source and said radiation detector, said computer configured to:

perform an initial full computed tomography scan of an area of interest in an object; and

perform at least one subsequent partial computed tomography scan of the area of interest to detect motion of a contrast agent.

13. (original) A system in accordance with Claim 12, wherein said computer further configured to:

perform a first full rotation including n sub-rotations, where no scanning is performed for all sub-rotations except an ith sub-rotation in which a scan is performed; and

perform a second full rotation including m sub-rotations where no scanning is performed for all sub-rotations except a jth sub-rotation in which a scan is performed.

14. (original) A system in accordance with Claim 13 wherein  $m = n$  and  $j = i$ .

15. (original) A system in accordance with Claim 13 wherein  $m = n$  and  $j \neq i$ .

16. (original) A system in accordance with Claim 13 wherein  $m \neq n$  and  $j = i$ .

17. (original) A system in accordance with Claim 13 wherein  $m \neq n$  and  $j \neq i$ .

18. (original) A system in accordance with Claim 12, wherein said computer configured to perform at least one subsequent partial scan comprises a computer configured to:

perform a first full rotation including  $n$  view-indexes, where no scanning is performed for all view-indexes except every  $i$ th view-index beginning with a view-index  $q$  in which a scan is performed; and

perform a second full rotation including  $m$  view-indexes where no scanning is performed for all view-indexes except every  $j$ th view-index beginning with a view-index  $r$  in which a scan is performed.

19. (original) A system in accordance with Claim 18 wherein  $r = q$ .

20. (original) A system in accordance with Claim 18 wherein  $r \neq q$ .

21. (currently amended) A computer readable medium encoded with a program configured to :

perform an initial full computed tomography scan of an area of interest in an object;  
and

perform at least one subsequent partial computed tomography scan of the area of interest to detect motion of a contrast agent.

22. (original) A computer readable medium in accordance with Claim 21 wherein said program further configured to instruct the computer to:

perform a first full rotation including  $n$  sub-rotations, where no scanning is performed for all sub-rotations except an  $i$ th sub-rotation in which a scan is performed; and

perform a second full rotation including  $m$  sub-rotations where no scanning is performed for all sub-rotations except a  $j$ th sub-rotation in which a scan is performed.

23. (original) A computer readable medium in accordance with Claim 21 wherein said program further configured to instruct the computer to:

perform a first full rotation including  $n$  view-indexes, where no scanning is performed for all view-indexes except every  $i$ th view-index beginning with a view-index  $q$  in which a scan is performed; and

perform a second full rotation including  $m$  view-indexes where no scanning is performed for all view-indexes except every  $j$ th view-index beginning with a view-index  $r$  in which a scan is performed.